

View Online at <https://aerobasegroup.com/nsn/4320-01-346-0029>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Dc

Media For Which Designed:

Water, fresh and water, salt

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

19.88 gallons per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

8.000 inches

Unpackaged Unit Width:

4.6880 inches

Unpackaged Unit Height:

5.688 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

4.0

Voltage In Volts:

12.0

Special Features:

Bilge type; automatic switch, discharge 1.125in.W/1193gph; monel shaft,

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400