

View Online at <https://aerobasegroup.com/nsn/4320-01-347-2822>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

40.0 gallons per minute

Discharge Pressure:

15.0 pounds per square inch gage

Total Head:

30.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

12.875 inches

Unpackaged Unit Width:

8.0000 inches

Unpackaged Unit Height:

9.375 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

4.9

Discharge Connection Thread Size And Series/type Designator:

1.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

0.750 horsepower

Voltage In Volts:

115.0

Phase:

Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400