NSN 4320-01-348-9518

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-348-9518

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Environmental Protection:
Dripproof
Pump Quantity:
1
Cooling Method:
Air to air cooled
End Application:
A/c system onboard 180 ft wlb c.G. Vessels
Maximum Discharge Flow Rate:
180.0 gallons per minute
Total Head:
150.000 feet
Operating Speed At Rated Capacity:
3600.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed

NSN 4320-01-348-9518Centrifugal Pump Unit - Page 2 of 2



Current Rating In Amps:	
22.0 and 11.0	
Discharge Connection Thread Size And Series/type Designator:	
1.500-11-1/2 npt	
ntake Connection Thread Size And Series/type Designator:	
2.000-11-1/2 npt	
Prime Mover Power Rating:	
7.500 horsepower	
Voltage In Volts:	
230.0 and 460.0	
Phase:	
Гһгее	
Frequency In Hertz:	
60.0	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A19400	