

View Online at <https://aerobasegroup.com/nsn/4320-01-353-8422>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Quick disconnect

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Splashtight

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

4610-01-219-8707

Maximum Discharge Flow Rate:

101.0 gallons per minute

Total Head:

102.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

End Item Name:

08355

Operation Relationship Design:

Simultaneous

Pump Basic Material:

Steel

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

16.9 and 8.5

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

5.0 horsepower

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Special Features:

Pump and motor already mounted into skid frame; 2 pull cables provided

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400