

View Online at <https://aerobasegroup.com/nsn/4320-01-353-8422>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Quick disconnect

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Splashtight

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**End Application:**

4610-01-219-8707

**Maximum Discharge Flow Rate:**

101.0 gallons per minute

**Total Head:**

102.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**End Item Name:**

08355

**Operation Relationship Design:**

Simultaneous

**Pump Basic Material:**

Steel

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

16.9 and 8.5

**Discharge Connection Thread Size And Series/type Designator:**

2.000-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

5.0 horsepower

**Voltage In Volts:**

220.0 and 440.0

**Phase:**

Three

**Special Features:**

Pump and motor already mounted into skid frame; 2 pull cables provided

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400