

View Online at <https://aerobasegroup.com/nsn/4320-01-358-8564>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Environmental Protection:**

Drip-proof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

55.0 gallons per minute

**Discharge Pressure:**

350.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Screw

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

73.375 inches

**Unpackaged Unit Width:**

22.5000 inches

**Unpackaged Unit Height:**

22.500 inches

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

30.0

**Prime Mover Power Rating:**

20.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Inlet, 150.0 lb 2.500 in. Plain face flange 7.000 in. Od four 0.750 in. Diameter holes on 5.500 in. Diameter bolt circle; outlet, 2.000 in. 300.0 lb raised face flange

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400