

View Online at <https://aerobasegroup.com/nsn/4320-01-358-8564>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Drip-proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

55.0 gallons per minute

Discharge Pressure:

350.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Screw

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

73.375 inches

Unpackaged Unit Width:

22.5000 inches

Unpackaged Unit Height:

22.500 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

30.0

Prime Mover Power Rating:

20.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Inlet, 150.0 lb 2.500 in. Plain face flange 7.000 in. Od four 0.750 in. Diameter holes on 5.500 in. Diameter bolt circle; outlet, 2.000 in. 300.0 lb raised face flange

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400