

View Online at <https://aerobasegroup.com/nsn/4320-01-359-2426>

Mounting Type:

Flange

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Media For Which Designed:

Hydrocarbon fuels and oils

End Application:

3930-01-330-8907, entwistle rough terrain fork lift truck

Maximum Discharge Flow Rate:

15.0 gallons per minute

Discharge Pressure:

2000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1150.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Splined, involute external

Drive Shaft Length:

1.141 inches

Unpackaged Unit Length:

5.160 inches

Unpackaged Unit Width:

5.200 inches

Unpackaged Unit Height:

5.110 inches

Pump Basic Material:

Steel

Discharge Connection Thread Size And Series/type Designator:

1.062 un

Intake Connection Thread Size And Series/type Designator:

1.312 un

Special Features:

Special oem design, ports on side are sae o-ring, -12un-2b; splined shaft 16/32 pitch; mtg falnge sae 2 bolt for engine mt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400