

View Online at <https://aerobasegroup.com/nsn/4320-01-362-5673>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Naphtha

Environmental Protection:

Explosion proof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

230.0 gallons per minute

Total Head:

125.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

12.1

Prime Mover Power Rating:

7.5 horsepower

Voltage In Volts:

460.0

Phase:

Three

Special Features:

3.000 in. Intake and 2.000 in. Discharge flange size

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400