

View Online at <https://aerobasegroup.com/nsn/4320-01-365-2560>

Mounting Type:

Flange

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Media For Which Designed:

Hydrocarbon fuels and oils

End Application:

750b crawler bulldozer tractor 1989, left-hand transmission control pump

Maximum Discharge Flow Rate:

5.790 gallons per minute

Discharge Pressure:

3000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

6000.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Splined, straight external

Drive Shaft End Diameter:

0.500 inches

Drive Shaft Length:

0.750 inches

Unpackaged Unit Length:

4.580 inches

Unpackaged Unit Width:

4.010 inches

Unpackaged Unit Height:

2.830 inches

Pump Basic Material:

Aluminum

Discharge Connection Thread Size And Series/type Designator:

0.562 un

Intake Connection Thread Size And Series/type Designator:

0.750-16 un

Special Features:

Internal gears steel; sae straight thd o-ring side ports; sae 2-bolt "aa" mounting flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400