

View Online at <https://aerobasegroup.com/nsn/4320-01-365-2907>

Mounting Type:

Flange

Cylinder Quantity:

9

Intake Connection Quantity:

1

Intake Connection Type:

Rectangular flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Rectangular flange

Drive Connection Type:

Rigid coupled

Pumping Element Type:

Piston

Maximum Discharge Flow Rate:

85.0 gallons per minute

Discharge Pressure:

2900.0 pounds per square inch gage

Operating Speed At Rated Capacity:

4300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Hydraulic cylinder

Control Location:

Center

Drive Shaft Type:

Splined, involute external

Unpackaged Unit Length:

12.050 inches

Unpackaged Unit Width:

8.1100 inches

Unpackaged Unit Height:

9.780 inches

Special Features:

Hydraulic displacement control (hdc) 14.5 - 60.0psi; standard pressure limiter range in ports a and b; mtg pad sae c w/ sealed cover; 1.00in.Dia side ports (per sae j518c code 61); shaft 14t 12/24pitch spline; hollow pistons; case drain port 1.0625-12npt; 108.Lb; 240.0deg f

Supplementary Features:

Charging pump 1.20cu in/rev, 350.0psi, inlet 1.3125-12npt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400