

View Online at <https://aerobasegroup.com/nsn/4320-01-366-9400>

**Mounting Type:**

Flange

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Square flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Rigid coupled

**Maximum Discharge Flow Rate:**

32.0 gallons per minute

**Discharge Pressure:**

2000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2950.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

0.875 inches

**Drive Shaft Length:**

2.440 inches

**Unpackaged Unit Length:**

14.320 inches

**Unpackaged Unit Width:**

5.120 inches

**Unpackaged Unit Height:**

5.380 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 un

**Special Features:**

Tandem gear pump; inlet port 1-1/2 split flange, 4ea 1/2-13unc-2b thd. 0.69in. Dp holes; key 1.25in. L x 0.25in.W; shaft notched 0.94in.L x 0.06in.Dp, opposite of keyway;

**Supplementary Features:**

Stud connectors

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400