

View Online at <https://aerobasegroup.com/nsn/4320-01-366-9438>

Thread Direction:

Right-hand

Torque Load Rating:

4081.0 inch-pounds

Mounting Type:

Flange

Width Across Flats:

0.750 inches

Mounting Hole Diameter:

0.540 inches

Mounting Hole Quantity:

2

Thread Size:

0.875-14 and 0.438-20

Operating Speed At Rated Capacity In Rpm:

328.0

Mounting Bolt Circle Diameter:

4.180 inches

Screw Thread Series Designator:

Unf

Shaft Rotation Direction:

Clockwise

Square End Length:

0.900 inches and 0.820 inches

Thread Location:

Internal

Connection Quantity:

1

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Temperature Range:

2750.0psi continuous and 3250.0psi intermittent at a known temperature

Connection Design:

Threaded

Displacement Type:

Constant

Constant Displacement Per Revolution:

10.600 cubic inches

Special Features:

Hex shaft both ends; motor 4.82in.L, 4.56in.H, 4.500in.W; mtg flange sae a-2 bolt, 5.12in.W; other end ears 2 places 180.0deg apart, with 0.500-13unc-28thd holes; ports sae 8 o-ring located on top; 7/16-20unf o-ring plug;

Supplementary Features:

18.4lbs; hydraulic fluid; operating temperature -40.0deg f to 125.0deg f

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f