

View Online at <https://aerobasegroup.com/nsn/4320-01-372-8136>

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Rectangular flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Rectangular flange

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Ethylene glycol or hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

17.0 gallons per minute and 11.0 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage and 2500.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute and 1200.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

0.875 inches

**Drive Shaft Length:**

2.312 inches

**Unpackaged Unit Length:**

12.120 inches

**Unpackaged Unit Width:**

7.000 inches

**Unpackaged Unit Height:**

7.125 inches

**Pump Basic Material:**

Steel

**Special Features:**

2.500 in. Diameter inlet; 1.000 in. And 0.750 in. Diameter outlet; outlet no. 2 45.0 degrees c/w from inlet

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400