

View Online at <https://aerobasegroup.com/nsn/4320-01-378-5719>

Prime Mover Quantity:

1

Mounting Type:

Frame

Cylinder Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Liquid

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Self ventilated

Discharge Pressure:

150.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Double acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Rotary

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

0.500 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

40 pgd, pulse-metering chemical pump; aluminum housing and kynar pump head; 1/4in.X 3/8in.Tubing suction connection; 1/4in.X 3/8in.Tubing threaded compression discharge connection; totally enclosed, fan cooled motor, pvc coated; stainless steel shaft; pvc impeller; polyethylene tank, 30.0gal, 22.562in.Dia x 22.312in.H; manual adjusting knob

Frequency In Hertz:

60.0

Supplementary Features:

2includes diaphragm pump, motor and tank; accessories furnished: 5.0ft tygon suction tubing, 10.0ft black polyethylene discharge tubing, ceramic suction sinker, polyproplene suction strainer, 1/2in.Npt poppet main connection, liquid level switch

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400