

View Online at <https://aerobasegroup.com/nsn/4320-01-378-5719>

**Prime Mover Quantity:**

1

**Mounting Type:**

Frame

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Self ventilated

**Discharge Pressure:**

150.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Double acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Rotary

**Control Location:**

Center

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Prime Mover Power Rating:**

0.500 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

40 pgd, pulse-metering chemical pump; aluminum housing and kynar pump head; 1/4in.X 3/8in.Tubing suction connection; 1/4in.X 3/8in.Tubing threaded compression discharge connection; totally enclosed, fan cooled motor, pvc coated; stainless steel shaft; pvc impeller; polyethylene tank, 30.0gal, 22.562in.Dia x 22.312in.H; manual adjusting knob

**Frequency In Hertz:**

60.0

**Supplementary Features:**

2includes diaphragm pump, motor and tank; accessories furnished: 5.0ft tygon suction tubing, 10.0ft black polyethylene discharge tubing, ceramic suction sinker, polyproplene suction strainer, 1/2in.Npt poppet main connection, liquid level switch

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400