

View Online at <https://aerobasegroup.com/nsn/4320-01-383-5162>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Air to air cooled

**End Application:**

4940-00-249-7315, cleaner, steam , pressurejet, trailer mounted

**Maximum Discharge Flow Rate:**

2.0 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Suction Lift:**

8.000 feet

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Double acting

**Operation Relationship Design:**

Simultaneous

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

0.25

**Discharge Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Voltage In Volts:**

230.0

**Special Features:**

Fan cooling, optional

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400