

View Online at <https://aerobasegroup.com/nsn/4320-01-383-5162>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Air to air cooled

End Application:

4940-00-249-7315, cleaner, steam , pressurejet, trailer mounted

Maximum Discharge Flow Rate:

2.0 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Suction Lift:

8.000 feet

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Double acting

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.25

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Voltage In Volts:

230.0

Special Features:

Fan cooling, optional

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400