NSN 4320-01-383-5310

Pump Shaft Sleeve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-383-5310

Over	all I	en	ath:
~~~	an L	-611	иит.

Between 5.4950 inches and 5.5000 inches

**Body Outside Diameter:** 

Between 3.7455 inches and 3.7460 inches

**Body Inside Diameter:** 

Between 3.0300 inches and 3.0600 inches

**End Application:** 

Los angeles class; nuclear reactor boundary area

Left Internal Flange Hole Diameter:

Between 3.0005 inches and 3.0010 inches

**Left Internal Flange Width:** 

1.2500 inches

**Interior Flange Hole Diameter:** 

Between 3.0005 inches and 3.0010 inches

**Interior Flange Left End To Centerline Distance:** 

3.4050 inches

**Interior Flange Width:** 

1.5700 inches

**Corner Shape:** 

Square outside right corner

**Criticality Code Justification:** 

Feat

**Surface Finish:** 

8.0 microinches outside diameter surface of body

**Keyway Dimension:** 

0.1795 inches internal keyway depth

**Special Features:** 

Free of mercury contamination; two holes 180.0 degrees apart 0.190-24 unc-3b 0.310 in. Full thread depth, 0.250-90.0 degrees c-sink; weapon system essential; aazp was 1d aao.19900; csyt was 1d da30.0

Material:

Titanium alloy uns r54810

**Material Specification:** 

Astm b367, gr c-5 assn standard single material response or astm b348, gr5 assn standard single material response

**Style Designator:** 

17c-1 solid, plain, no outside flanges, internal flange one end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A045a0