

View Online at <https://aerobasegroup.com/nsn/4320-01-383-5384>

**Mounting Type:**

Base

**Cylinder Quantity:**

3

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Water, fresh

**Pumping Element Type:**

Piston

**End Application:**

4940-00-249-7315 trailer mounted pressure jet steam cleaner

**Maximum Discharge Flow Rate:**

4.5 gallons per minute

**Discharge Pressure:**

2000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1125.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Double acting

**Reciprocating Stroke Type:**

Fixed

**Operation Method:**

Powered

**Drive Shaft Type:**

Machine keyway

**Drive Shaft End Diameter:**

0.945 inches

**Drive Shaft Length:**

1.200 inches

**Unpackaged Unit Length:**

11.400 inches

**Unpackaged Unit Width:**

9.900 inches

**Unpackaged Unit Height:**

6.900 inches

**Discharge Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Special Features:**

Max. Fluid temp 165.0deg.F; bore 0.787in.; stroke 0.630in.; crankcase cap 33.8oz

**Supplementary Features:**

Aka triplex plunger pump

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400