

View Online at <https://aerobasegroup.com/nsn/4320-01-383-5384>

Mounting Type:

Base

Cylinder Quantity:

3

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Media For Which Designed:

Water, fresh

Pumping Element Type:

Piston

End Application:

4940-00-249-7315 trailer mounted pressure jet steam cleaner

Maximum Discharge Flow Rate:

4.5 gallons per minute

Discharge Pressure:

2000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1125.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Double acting

Reciprocating Stroke Type:

Fixed

Operation Method:

Powered

Drive Shaft Type:

Machine keyway

Drive Shaft End Diameter:

0.945 inches

Drive Shaft Length:

1.200 inches

Unpackaged Unit Length:

11.400 inches

Unpackaged Unit Width:

9.900 inches

Unpackaged Unit Height:

6.900 inches

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Special Features:

Max. Fluid temp 165.0deg.F; bore 0.787in.; stroke 0.630in.; crankcase cap 33.8oz

Supplementary Features:

Aka triplex plunger pump

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400