

View Online at <https://aerobasegroup.com/nsn/4320-01-385-1243>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

36.0 gallons per minute

**Discharge Pressure:**

150.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Length:**

25.875 inches

**Unpackaged Unit Width:**

11.7500 inches

**Unpackaged Unit Height:**

18.062 inches

**Pump Basic Material:**

Bronze

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Prime Mover Power Rating:**

10.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Special Features:**

Ports internally threaded with bronze nipples and flanges, suction 2.0in. W/four 3/4in.Dia holes on 4-3/4in.Bc, discharge 1-1/2in/ w/four 5/8in.Dia holes on 3-7/8in/bc

**Frequency In Hertz:**

60.0

**Supplementary Features:**

Base 23.0in.L x 22.0in.W; w/shock mounts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400