NSN 4320-01-385-7015

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-385-7015

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Flange
Intake Connection Quantity:
1
Intake Connection Type:
Unthreaded external
Discharge Connection Quantity:
1
Discharge Connection Type:
Unthreaded external
Current Type:
Dc
Media For Which Designed:
Ethylene glycol
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
26.7 liters per minute
Discharge Pressure:
10.0 kilograms per square centimeter gage
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
1.0
Prime Mover Power Rating:
25.0 watts

NSN 4320-01-385-7015

Centrifugal Pump Unit - Page 2 of 2



Voltage	In \	Volts:
---------	------	--------

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400