

View Online at <https://aerobasegroup.com/nsn/4320-01-386-2523>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

3.2

**Features Provided:**

Self-priming

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

27in. Long sealless drum pump made of polypropylene; tube od is 2in.; maximum temperature is 160deg; can handle aggressive liquids, acids and other corrosives up to 500cps and 1.8sg; up to 80ft discharge head

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400