

View Online at <https://aerobasegroup.com/nsn/4320-01-386-6429>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

40.0 gallons per minute

**Operating Speed At Rated Capacity:**

10000.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

3.2

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.50 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

36in. Long drum pump made of stainless steel; tube od is 2in.; temperature is 220deg f; can handle non-corrosive chemicals and oils up to 550cps and 1.8 sg; up to 80ft discharge head; tefc motor for corrosive fumes

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400