

View Online at <https://aerobasegroup.com/nsn/4320-01-386-6429>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

40.0 gallons per minute

Operating Speed At Rated Capacity:

10000.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

3.2

Features Provided:

Self-priming

Prime Mover Power Rating:

0.50 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

36in. Long drum pump made of stainless steel; tube od is 2in.; temperature is 220deg f; can handle non-corrosive chemicals and oils up to 550cps and 1.8 sg; up to 80ft discharge head; tefc motor for corrosive fumes

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400