

View Online at <https://aerobasegroup.com/nsn/4320-01-387-7299>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

10.0 gallons per minute

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

3.0 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

36in. Long high viscosity drum pump; has 3 polytetrafluoroethylene screws mounted on s/s outer tube; tube o/d is 2in.; can handle foods, polymer, adhesives, oils, resins, etc. With viscosities up to 15000 cps; temperature is 200deg f; discharge head up to 200ft

Frequency In Hertz:

60.0

Supplementary Features:

Tefc "t" series motor, double insulated, handle with built-in switch, thermal overload, manual reset, 12ft, 3-wire cord with plug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400