

View Online at <https://aerobasegroup.com/nsn/4320-01-388-0533>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

5.0 gallons per minute

**Operating Speed At Rated Capacity:**

10000.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Screw

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

3.2

**Prime Mover Power Rating:**

0.5 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

27in. Long lab duty pump with 1in. Diameter constructed out of cpvc, polytetrafluoroethylene and inconel; temperature 150deg f; for transferring corrosive acids and alkalines from small glass container carboys up to 1.4 specific gravity and 200 cps viscosity

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400