

View Online at <https://aerobasegroup.com/nsn/4320-01-388-0533>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

5.0 gallons per minute

Operating Speed At Rated Capacity:

10000.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

3.2

Prime Mover Power Rating:

0.5 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

27in. Long lab duty pump with 1in. Diameter constructed out of cpvc, polytetrafluoroethylene and inconel; temperature 150deg f; for transferring corrosive acids and alkalines from small glass container carboys up to 1.4 specific gravity and 200 cps viscosity

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400