

View Online at <https://aerobasegroup.com/nsn/4320-01-388-1271>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Flange

Current Type:

Ac

Environmental Protection:

Vaporproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

14.0 gallons per minute

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Vane

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.6

Prime Mover Power Rating:

0.25 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

4-blade turbine tube mixer for mixing or blending in a 55-gal drum; mixer tube is 36in. Long and 2in. In diameter made of 316 s/s and polytetrafluoroethylene; maximum temperature is 200deg f.; viscosities up to 1000 cps; s/s turbine draws liquid into mixer tube at the top of drum and forces it out the bottom; optional static protection kit p/n a100961 available for mixing flammable or combustible liquids

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400