

View Online at <https://aerobasegroup.com/nsn/4320-01-388-1271>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Flange

**Current Type:**

Ac

**Environmental Protection:**

Vaporproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

14.0 gallons per minute

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Vane

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.6

**Prime Mover Power Rating:**

0.25 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

4-blade turbine tube mixer for mixing or blending in a 55-gal drum; mixer tube is 36in. Long and 2in. In diameter made of 316 s/s and polytetrafluoroethylene; maximum temperature is 200deg f.; viscosities up to 1000 cps; s/s turbine draws liquid into mixer tube at the top of drum and forces it out the bottom; optional static protection kit p/n a100961 available for mixing flammable or combustible liquids

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400