

View Online at <https://aerobasegroup.com/nsn/4320-01-388-1601>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Environmental Protection:

Vaporproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

10.0 gallons per minute

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Rotary Pump Design:

Screw

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.6

Prime Mover Power Rating:

0.25 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Tefc motor; up to 10ft discharge head; can handle aggressive liquids or corrosive environments; motor has 12ft, 3-wire cord and plug, csa approved; liquids to 400 cps and 1.8 s.G.; temperature 150deg f; pump length 27in., cpvc tube with 1.625in. O/d

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400