

View Online at <https://aerobasegroup.com/nsn/4320-01-388-1614>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Environmental Protection:**

Vaporproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

10.0 gallons per minute

**Operating Speed At Rated Capacity:**

3450.0 revolutions per minute

**Pumping Element Operating Position:**

Vertical

**Rotary Pump Design:**

Screw

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.6

**Prime Mover Power Rating:**

0.25 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Pump length is 27in., 316 stainless steel tube with 1.5in. O/d; tefc motor; up to 10ft discharge head; can handle aggressive liquids or corrosive environments; motor has 12ft, 3-wire cord and plug, csa approved; liquids to 400 cps and 1.8 s.G.; temperature is 150deg

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400