

View Online at <https://aerobasegroup.com/nsn/4320-01-388-4755>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

2

Discharge Connection Type:

Unthreaded external

Current Type:

Ac

Media For Which Designed:

Photographic developers

Environmental Protection:

Dripproof

Pump Quantity:

2

Cooling Method:

Air to air cooled

End Application:

For use with eastman kodak m35 x-omat processor

Maximum Discharge Flow Rate:

6.7 gallons per minute

Total Head:

16.100 feet

Operating Speed At Rated Capacity:

34.5 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

2

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

1.6

Features Provided:

Self-priming

Prime Mover Power Rating:

0.125 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Dual head seal-less magnetic drive pump ceramic magnet

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400