

View Online at <https://aerobasegroup.com/nsn/4320-01-388-4755>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Unthreaded external

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Unthreaded external

**Current Type:**

Ac

**Media For Which Designed:**

Photographic developers

**Environmental Protection:**

Dripproof

**Pump Quantity:**

2

**Cooling Method:**

Air to air cooled

**End Application:**

For use with eastman kodak m35 x-omat processor

**Maximum Discharge Flow Rate:**

6.7 gallons per minute

**Total Head:**

16.100 feet

**Operating Speed At Rated Capacity:**

34.5 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Current Rating In Amps:**

1.6

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.125 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Dual head seal-less magnetic drive pump ceramic magnet

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400