

View Online at <https://aerobasegroup.com/nsn/4320-01-388-4787>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Pump Quantity:

1

Maximum Discharge Flow Rate:

200.0 gallons per minute

Discharge Pressure:

32.0 pounds per square inch gage

Total Head:

90.000 feet

Suction Lift:

16.000 feet

Operating Speed At Rated Capacity:

3400.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Diesel engine

Discharge Connection Thread Size And Series/type Designator:

2.000-11.5 npt

Intake Connection Thread Size And Series/type Designator:

2.000-11.5 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

7.0 horsepower

Special Features:

Can handle 0.75in. Diameter spherical solids

Supplementary Features:

Pump size 2"x2" npt female, casing aluminum no.356-t6 with cast iron cut-water insert

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400