

View Online at <https://aerobasegroup.com/nsn/4320-01-393-5921>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Unthreaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Unthreaded external

Current Type:

Dc

Media For Which Designed:

Water, fresh or water, salt

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

7.1 gallons per minute

Discharge Pressure:

10.0 kilograms per square centimeter gage

Total Head:

3.300 feet

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

6.693 inches

Unpackaged Unit Width:

2.6970 inches

Unpackaged Unit Height:

2.953 inches

Pump Basic Material:

Plastic

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

0.9

Prime Mover Power Rating:

0.001 horsepower

Voltage In Volts:

24.0

Special Features:

Continuous operation motor in temperature range of m40.0 degrees f to 212.0 degrees f; motor bracket can be turned through a full 360.0 degrees to facilitate installation; 19.0 mm or 3/4 in. Hose size connections

Supplementary Features:

Has 2 lead wires 260.0 mm long

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400