

View Online at <https://aerobasegroup.com/nsn/4320-01-395-5256>

**Mounting Type:**

Flange

**Cylinder Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Rigid coupled

**Pumping Element Type:**

Piston

**End Application:**

170ft coastal patrol

**Maximum Discharge Flow Rate:**

10.0 gallons per minute

**Discharge Pressure:**

3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Counterclockwise

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Volume Control Type:**

Pressure compensation

**Drive Shaft Type:**

Key type, external

**Drive Shaft End Diameter:**

0.875 inches

**Drive Shaft Length:**

1.875 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.250-12 unf

**Special Features:**

Buna n seals; adjustment screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400