## NSN 4320-01-396-7769

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-396-7769

Manustina Tuna.
Mounting Type:
Flange
Intake Connection Quantity:
1
Intake Connection Type:
Rectangular flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Rectangular flange
Drive Connection Type:
Rigid coupled
Media For Which Designed:
Hydrocarbon fuels and oils
End Application:
Weapon system code ac, support equipment, b-1 aircraft
Maximum Discharge Flow Rate:
23.09 gallons per minute
Discharge Pressure:
3500.0 pounds per square inch gage
Operating Speed At Rated Capacity:
2800.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Pump Rotation Direction:
Clockwise
Rotary Pump Design:
Vane
Operation Method:
Powered
Drive Shaft Type:
Machine keyway
Drive Shaft End Diameter:
0.875 inches
Drive Shaft Length:
2.190 inches
Special Features:
Single pimp; both ports located aligned on top of pump, suction 1.5in.Dia, pressure 1.00in.Dia; seal s5; 2 bolt sae b mtg flange
Supplementary Features:
34.0lb; maximum 4000.0psi
Shelf Life:
N/a

## NSN 4320-01-396-7769

Rotary Pump - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A19400