

View Online at <https://aerobasegroup.com/nsn/4320-01-397-7870>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, distilled

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Weapon system code jk, wasp class lhd

Maximum Discharge Flow Rate:

120.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3585.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

35.850 inches

Unpackaged Unit Width:

20.0000 inches

Unpackaged Unit Height:

16.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.730

Prime Mover Power Rating:

25.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Includes: lifting eye and vent valve; impeller 8-7/8

Frequency In Hertz:

60.0

Supplementary Features:

Demineralized water colling pump, 1-1/4 x 2 x 9

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400