

View Online at <https://aerobasegroup.com/nsn/4320-01-398-4566>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh and water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Weapons system, 170' coastal patrol

Maximum Discharge Flow Rate:

315.0 gallons per minute

Discharge Pressure:

150.0 pounds per square inch gage

Total Head:

250.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

3550.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

28.0

Prime Mover Power Rating:

30.0 horsepower

Voltage In Volts:

460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400