

View Online at <https://aerobasegroup.com/nsn/4320-01-407-5146>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Discharge Pressure:

100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

17.000 inches

Unpackaged Unit Width:

5.0000 inches

Unpackaged Unit Height:

8.000 inches

Pump Basic Material:

Iron, cast

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

1.62

Prime Mover Power Rating:

1.0 horsepower

Voltage In Volts:

208.0 and 230.0 and 460.0

Phase:

Three

Special Features:

Back pull-out feature; npt connections; 32.0deg -212.0deg f maximum operating temp; 1-1/4 x 1-1/2 x 5 pump size; 5.11in. Impeller; clockwise rotation

Frequency In Hertz:

60.0

Supplementary Features:

Bronze fitted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400