

View Online at <https://aerobasegroup.com/nsn/4320-01-407-5146>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Discharge Pressure:**

100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

17.000 inches

**Unpackaged Unit Width:**

5.0000 inches

**Unpackaged Unit Height:**

8.000 inches

**Pump Basic Material:**

Iron, cast

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

1.62

**Prime Mover Power Rating:**

1.0 horsepower

**Voltage In Volts:**

208.0 and 230.0 and 460.0

**Phase:**

Three

**Special Features:**

Back pull-out feature; npt connections; 32.0deg -212.0deg f maximum operating temp; 1-1/4 x 1-1/2 x 5 pump size; 5.11in. Impeller; clockwise rotation

**Frequency In Hertz:**

60.0

**Supplementary Features:**

Bronze fitted

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400