

View Online at <https://aerobasegroup.com/nsn/4320-01-407-7563>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Air to air cooled

End Application:

W/s, usns henry j. Kaiser

Maximum Discharge Flow Rate:

0.08 gallons per minute

Discharge Pressure:

100.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Volume Control Type:

Hydraulic cylinder

Control Location:

Right side

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.4

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.25 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Field adjustable hydraulic relief valve; automatic air venting on each stroke, self-compensating hydraulic system, large single ball check

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400