NSN 4320-01-408-7042



Hydraulic Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4320-01-408-7042 **Thread Direction:** Right-hand **Torque Load Rating:** 190.0 inch-pounds **Key Length:** 1.630 inches **Mounting Type:** Flange **Key Width:** 0.190 inches **Mounting Hole Diameter:** 0.440 inches **Mounting Hole Quantity: Thread Size:** 1.062-12 and 0.438-20 **Shaft Diameter:** 0.750 inches **Operating Speed At Rated Capacity In Rpm:** 4000.0 **Mounting Bolt Circle Diameter:** 4.192 inches **End Application:** De-icing, aircraft **Drive Shaft Type:** Keyed **Housing Material:** Iron, cast **Screw Thread Series Designator:**

Un

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal

Shaft Protrusion Length:

2.190 inches

Connection Quantity:

3

Connection Type:

Inlet and outlet and drain

Maximum Working Pressure Rating At Specificationified Tempurature Range:

2500psi at rated temperature range

NSN 4320-01-408-7042 Hydraulic Motor - Page 2 of 2



Connection Design:
Threaded
Key Height:
0.190 inches
Displacement Type:
Constant
Constant Displacement Per Revolution:
0.738 cubic inches
Mounting Bolt Hole Spacing:
4.192 center to center
Special Features:
65psi maximum case drain pressure
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
T103-f