

View Online at <https://aerobasegroup.com/nsn/4320-01-411-0711>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Hand truck

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

400.0 gallons per minute

Total Head:

90.000 feet

Suction Lift:

25.000 feet

Operating Speed At Rated Capacity:

3300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Pump Basic Material:

Iron, cast

Prime Mover Type:

Diesel engine

Discharge Connection Thread Size And Series/type Designator:

3.000-8 npt

Intake Connection Thread Size And Series/type Designator:

3.000-8 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

11.0 horsepower

Special Features:

Hand crank starting; 4.0 hrs running time per tank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400