

View Online at <https://aerobasegroup.com/nsn/4320-01-411-0711>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Hand truck

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

400.0 gallons per minute

**Total Head:**

90.000 feet

**Suction Lift:**

25.000 feet

**Operating Speed At Rated Capacity:**

3300.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Pump Basic Material:**

Iron, cast

**Prime Mover Type:**

Diesel engine

**Discharge Connection Thread Size And Series/type Designator:**

3.000-8 npt

**Intake Connection Thread Size And Series/type Designator:**

3.000-8 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

11.0 horsepower

**Special Features:**

Hand crank starting; 4.0 hrs running time per tank

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400