

View Online at <https://aerobasegroup.com/nsn/4320-01-411-2168>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

500.0 gallons per minute

Discharge Pressure:

30.0 pounds per square inch gage

Total Head:

68.000 feet

Suction Lift:

3.000 feet

Operating Speed At Rated Capacity:

1790.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

11.5

Prime Mover Power Rating:

11.7 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

Sea water cooling pump; navy standard close-coupled pump

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400