

View Online at <https://aerobasegroup.com/nsn/4320-01-411-4904>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

60.0 gallons per minute

**Total Head:**

140.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

0.71

**Discharge Connection Thread Size And Series/type Designator:**

0.750-14 npt

**Intake Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Prime Mover Power Rating:**

0.75 horsepower

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Close coupled centrifugal pump; mechanical seal, ni-al bronze construction

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400