

View Online at <https://aerobasegroup.com/nsn/4320-01-412-7583>

Mounting Type:

Flange

Cylinder Quantity:

11

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Media For Which Designed:

Hydrocarbon fuels and oils

Pumping Element Type:

Piston

End Application:

1740-00-143-8464

Maximum Discharge Flow Rate:

25.6 gallons per minute

Discharge Pressure:

3600.0 pounds per square inch gage

Operating Speed At Rated Capacity:

2200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Drive Shaft Type:

Splined, involute external

Drive Shaft Length:

1.320 inches

Discharge Connection Thread Size And Series/type Designator:

1.3125-12 unf

Intake Connection Thread Size And Series/type Designator:

1.875-12 unf

Special Features:

Remote control port 0.4375-20 unf-2b straight thread o-ring sae-4; optional drain port 0.875-14 unf-2b straight thread o-ring sae-10; pressure compensator setting 2500 psi -0/plus 150 psi; pressure differential setting 150 psi set by factory a6 1/2 maximum flow; mounting flange 2 bolt sae 'b'

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400